


**Polystone®**  
Thermoplastics

**Polystone® M (UHMW-PE)**  
Setting the pace in today's industry




## The pursuit of customer satisfaction



„I can assist you in choosing the best Polystone® M for your application.“

As a major manufacturer of Polystone® M (ultra-high molecular weight polyethylene), Röchling Engineered Plastics is among the world's leading suppliers to the conveying, material handling and packaging industries. Our sales and engineering teams work closely to provide you with the best solution to improve your business performance.

Quick to respond to the needs of our customers, we are constantly pursuing new and improved product designs and manufacturing techniques, allowing us to supply a state-of-the-art product at the most economical price. From conveyor wear parts to truck bedliners, Polystone® M keeps it moving.



**Quality · Service ·  
Dependability · Inventory**

## Polystone® M (UHMW-PE): Designed for performance

Polystone® M is a highly versatile polymer that can be designed and formulated to meet your industrial needs. Stocked as sheets, rods, tubes and profiles, it can be machined for your specific application.

Why industrial engineers prefer Polystone® M:

- low coefficient of friction
- excellent abrasion resistance
- high-impact strength (will not break or shatter)
- chemical resistance
- FDA and USDA accepted
- broad temperature range (-450° to + 180° F)
- little or no moisture absorption
- noise resistance
- easy to machine




Polystone® M Selection Table	Material Description	Standard Color
Virgin Natural	Standard UHMW-PE, FDA/USDA approved	Opaque white
Virgin Colors	Available in standard and custom colors	Assorted
Reprocessed	Economical benefit in non-food applications	Black, Green
XL Crosslinked	Improved wear resistance and reduced thermal expansion	Grey
MPG Glass Filled	Superior wear resistance and dimensional stability	Blue
M-Slide	Dry lubricants to significantly reduce the coefficient of friction	Dark Grey
Oil Filled	Reduced coefficient of friction, FDA/USDA approved	Grey
U.V. Stabilized	Life can be extended up to 5 times in outdoor applications	Black
Anti-Static	Electrically conductive to reduce static build-up	Black
Rubber Backed	.060" rubber backing allows the use of adhesives	Opaque white
Flame Retardant	MSHA approved for underground mining	White

*Other grades and colors available upon request*

# Polystone® M is extremely durable in the food and beverage, bottling and canning industries

The excellent abrasion and chemical resistance in addition to the ability to absorb noise makes it ideal for applications such as:

- star wheels and corner guides
- chain and belt guides
- idler sprockets
- guide rails and rollers
- bin and mixer linings



1 Polystone® M star wheels and guides on filling and capping machinery  
2 Polystone® M chain guides and tracks on food packaging machinery



## Polystone® M resists abrasion in the conveying industry

Today's high speed conveyors demand surfaces with a low coefficient of friction combined with excellent impact and abrasion resistance. Polystone® M is ideal for the following applications:


- straight and curved tracks
- wear strips and guide rails
- rollers and roller sleeves
- gears and sprockets
- pillow blocks




3





4



5



6



7

- 3 Polystone® M machined and extruded chain tracks  
 4 Machined curve tracks and extruded profiles of Polystone® M  
 5 Polystone® M chain guide and roller  
 6 Polystone® M Oil Filled chain tensioner  
 7 Polystone® M guide rails  
 8 Car wash roller machined from Polystone® M Reprocessed




5

## Polystone® M promotes flow in the material handling industry

Moving and conveying materials presents engineers with the challenge of finding a solution to abrasion and sticking problems. Polystone® M is the answer in applications such as:

- drag flights and paddles
- truck bedliners
- side rails and skirtboards
- dragline bucket liners



9



11



10






12

- 9 Polystone® M U.V. Stabilized dock fenders  
 10 Chain wear plates made of Polystone® M Reprocessed  
 11 Polystone® M wear pads on an impact slider bed  
 12 A truck bedliner made of Polystone® M

# Polystone® M performs with remarkably low friction in the packaging industry

A polymer that is self-lubricating, non-marking and very easily machined while continuing to exhibit its exceptional abrasion resistance makes it extremely attractive in applications such as:

- bushings and bearings
- timing screws
- drive sprockets
- bumper and sorter push blocks
- wear strips and plates



13 Polystone® M star wheels and guides  
 14 Wear components machined from Polystone® M  
 15 A brewery makes use of Polystone® M wear strips and rollers  
 16 A timing screw machined from Polystone® M Natural



# Chemical resistance

## Machining methods

Chemical resistance	Polystone® M (UHMW-PE)		Polystone® M (UHMW-PE)
Acetaldehyde	+	Glycerine	+
Acetic acid	+	Hydrochloric acid	+
Acetone	+	Hydrogen peroxide	+
Acrylonitrile	+	Hydrogen sulphide	+
Allyl alcohol	96 +	Lactic acid	+
Aluminum chloride	A +	Magnesium chloride	A +
Ammonia	A +	Mercury	+
Ammonium chloride	A +	Methanol	+
Aniline	+	Methyl ethyl ketone	+
Benzaldehyde	+	Methylene chloride	/
Benzene	/	Mineral Oil	+
Benzyl alcohol	+	Nitric acid	+ to /
Bleach (Chlorine)	-	Nitrobenzene	+
Boric acid	A +	Oleic acid	+
Butanol	+	Ozone	/
Butyl acetate	+	Perchloric acid	50 +
Calcium chloride	+	Petroleum	+
Carbon disulphide	/	Phenol	+
Carbon tetrachloride	/ M -	Phosphoric acid	+
Chlorine gas	/	Potassium bichromate	40 +
Chlorobenzene	/	Potassium hydroxide	30 +
Chloroform	/ M -	Potassium nitrate	+
Chromic acid	10 +	Potassium permanganate	+
Citric acid	+	Pyridine	+
Cyclohexanol	+	Sea water	+
Cyclohexanone	+	Sodium carbonate	10 +
Dekalin	+	Sodium chloride	10 +
Dibutyl phthalate	+	Sodium hydroxide	60 +
Diesel oil	+	Sodium sulphite	
Diethyl ether	+ to /	Sulphuric acid	75 +
Dioxane	+	Tallow	+
Ethanol	96 +	Tetrahydrofurane	+ M -
Ethyl acetate	+	Tetralin	+
Ethylene chloride	/	Thionyl chloride	-
Ethylene diamine	+	Toluene	/
Ferric chloride	A +	Transformer oil	+
Fluorine	-	Trichlorethylene	+ M -
Formaldehyde	40 +	Urea, aqueous	33 +
Formic acid	+	Water	+
Furfural	+	Zinc chloride	A +

Values obtained at room temperature. Call for high or low temperature applications.

Number indicates concentration if < 100 %. M = Values may change under mechanical stress.

A = Aqueous solution.

+ = Specimen is resistant .....Swelling < 3% or weight loss < 0.5%. Break elongation not significantly altered.

/ = Specimen has limited resistance .....Swelling 3-8% or weight loss 0.5-5% and/or break elongation decreased by < 50%.

- = Specimen is not resistant .....Swelling > 8% or weight loss > 5% and/or break elongation decreased by > 50%.

## Recommended Machining Conditions


Polystone® M can be efficiently machined with equipment generally used for fabricating wood and metals. Sharp tools with wide-tooth spacing should be used for sufficient chip clearance and heat removal.

### Sawing




Cutting speed	3,000 - 13,000 ft/min
Feed	0.0008 - 0.0040 in/tooth
Rake angle in degrees	0 - 5 HM, 3 - 8 HSS
Clearance in degrees	10 - 15 HM, 30 - 40 HSS
Tool material	Carbide Tip High speed tool steel (HSS)
Comments	pitch 0.20 - 0.40 in setting 0.03 - 0.04 in

### Turning




Cutting speed	600 - 1,300 ft/min
Feed	0.004 - 0.020 in/rev
Rake angle in degrees	0 - 15
Clearance in degrees	5 - 15
Tool material	HSS
Comments	depth of cut .020 - .250 in

### Milling




Cutting Speed	600 - 12,000 ft/min
Feed	0.010 - 0.030 in/rev
Rake angle in degrees	0 - 15
Clearance in degrees	5 - 15
Tool material	HSS
Comments	---

### Planing



Cutting speed	8,000 - 12,000 ft/min
Feed	0.012 - 0.030 in/rev
Rake angle in degrees	15 - 20
Clearance in degrees	15 - 30
Tool material	HSS, carbide Tip
Comments	---

### Drilling



Cutting speed	150 - 500 ft/min
Feed	0.004 - 0.012 in/rev
Rake angle in degrees	15 - 25
Clearance in degrees	10 - 12
Tool material	Hardened tool steel
Comments	rifling angle 20 - 30° angle of point 60 - 90°



# Range of products

## Physical properties and specifications

Physical properties			Polystone M® (UHMW-PE)				
Property	Units	ASTM Test	Natural	XL Cross linked	MPG Glass filled	Reprocessed	
Density	gm/cm <sup>3</sup>	D792	.930 - .936	.932	.96	.935	
Tensile strength at yield 73°F	psi	D638	3100	2900	2700	3000	
Elongation 73° F	%	D638	350	300	300	300	
*Relative volumetric abrasion loss	*	*	100	85	75	90	
Coefficient of friction 73°F on steel	-	-	Static	.15 - .20	.15 - .20	.15 - .20	.17 - .20
			Dynamic	.10 - .20	.10 - .20	.10 - .20	.10 - .20
IZOD impact strength 73°F	KJ/m <sup>2</sup>	D4020-96	125	125	110	96	
Hardness 73°F	-	D785	Shore D 62 - 66	D 62 - 67	D 62 - 67	D 63 - 69	
Melting point	°F	D789	275° - 280°	275° - 280°	275° - 280°	275° - 280°	
Coefficient of linear thermal expansion	1/K	D696	2.0 x 10 <sup>-4</sup>	1.0 x 10 <sup>-4</sup>	1.0 x 10 <sup>-4</sup>	1.9 x 10 <sup>-4</sup>	
Continuous service temperature in air (max)	°F	-	180	180	180	180	
Volume resistivity	Ohm/cm	D257	>10 <sup>15</sup>	>10 <sup>15</sup>	>10 <sup>15</sup>	>10 <sup>15</sup>	
Dielectric constant (10 <sup>3</sup> Hz)	-	D150	2.3	2.3	2.3	-	
Dielectric strength	KV/mm	D149	900	900	900	900	

### Polystone® M (UHMW-PE)

#### Sheets

1/32" - 7" x 48" x 120"  
1/32" - 4" x 48" x 96"

#### Rods




1/4" - 10" diameter

#### Tubes

2" - 7-1/8" outside diameter

#### Profiles

Standard and custom



### Specifications and Approvals

ASTM	D-4020	UHMW-PE molding and extrusion materials
FDA	Natural, Oil-filled and if requested, Virgin Colors	Polystone® M (UHMW-PE) is in compliance with FDA regulations as listed in the Federal Register under the Food, Drug and Cosmetic Act of 1958, as amended for food contact use provided it is used unmodified and in accordance with good manufacturing practices.
USDA	Same as above	Polystone® M (UHMW-PE) has USDA approval for meat and poultry in food handling applications.
Federal	L-P-390C	Plastic, molding and extrusion material, polyethylene and copolymers (low, medium and high density)
Military	MIL-P-23536 MIL-P-21922	Plastic sheets, virgin and borated polyethylene Plastic rods and tubes polyethylene
OSHA		Polystone® M (UHMW-PE) is not considered hazardous, as defined by the OSHA Hazard Communications Standard 29 CFR 1910.1200

\* Industry standard testing method using a slurry of 60 % aluminum oxide and 40 % water at a rotation speed of 1750 rpm for 2 hours. Results indicate the ability of each material, in relation to Natural (=100), to resist abrasion under typical UHMW-PE applications. A lower number indicates better abrasion resistance.

The information listed herein is stated to the best of our knowledge and is intended to provide a general guideline for Polystone® M and its uses. The values given are based on laboratory testing backed with global industry experience. All properties in this brochure have performed equal or better in laboratory testing. However, the data should not be considered as guaranteed specific properties. Suggested applications are provided for information only and are not specific recommendations.

# Röchling, the international leader in plastics manufacturing and fabricating

Companies within the Röchling Haren group:

## EUROPE

Röchling Haren KG, Haren/Germany  
Röchling Materials Ltd., Stonehouse/Great Britain  
Röchling Engineering Sarl, Maxéville/Lyon/France  
Permal Composites S.A., Maxéville/France  
Röchling Technische Kunststoffe KG, Lützen/Germany  
Leripa Kunststoff GmbH & Co. KG, Rohrbach/Austria  
Blumer Srl, Arcisate/Italy

## USA

Röchling Engineered Plastics/USA East/ West  
Röchling Machined Plastics, Mount Pleasant, PA/ USA

## FAR-EAST

Röchling Engineering Plastics, Singapore



## East

### Röchling Engineered Plastics

P.O. Box 2729  
Gastonia, NC 28053-2729  
Tel: 704-922-7814  
Fax: 704-922-7651  
**800-541-4419**  
[www.roechling-plastics.us](http://www.roechling-plastics.us)  
[rep@roechling-plastics.us](mailto:rep@roechling-plastics.us)



## West

### Röchling Engineered Plastics

2040 Carlos Avenue  
Ontario, CA 91761  
Tel: 909-923-6601  
Fax: 909-923-3280  
**800-545-5177**  
[www.roechling-plastics.us](http://www.roechling-plastics.us)